

SPECIFICATION SHEET

Photo



Product Information:

Item Descriptions:	3-in-1 set for WC, 1.13 m installation height
Model:	RAPID SL
Article No.	38772001
Material:	Various Material
Brand:	GROHE
Finish:	
Note:	The colour / finish may vary on actual

Specifications:

Grohe Rapid SL 3 in 1-Set for Toilet Cistern GD 2

with small maintenance opening
1.13 m installation height
for on-the-wall installations or studded walls
powder-coated steel frame, self-supporting
for dry-cladding, completely pre-assembled
with fixed connections
for single or series installation
quick adjustment, lockable height
set of fittings
TÜV approved
2 toilet fixing bolts
fixing device for ceramic object
distance of fixing bolts 180/230 mm
PP outlet bend Ø 80 mm
depth adjustable reducer Ø 80/100 mm
inlet and outlet connecting set
cistern GD 2, 6-9 l
adjustment ex factory 6l and 3l
pneumatic discharge valve offering 2 modes of operation:
- dual flush
- start/stop flush
water supply from left/right or back
fittings group I
DIN approved
insulated against condensation
water supply connection 1/2" with including integrated angle
valve and push fit flexible hose union, no tools required for
the installation of the inspection shaft including protection
during construction phase, for vertical or horizontal use)
Grohe Flush Plate Skate Cosmopolitan, Chrome
dual flush or start/stop flush
vertical installation
durable chrome surface, easy to clean (GROHE StarLight®)
save water with maximum comfort (GROHE EcoJoy®)
dimensions: 156 x 197 mm
Wall-Mounting
for on-the-wall installation
for the attachment of the elements to masonry or in front of
studded walls
continuous depth adjustment from 130 - 230 mm
panel support for single or rail installation

TECHNICAL DRAWING

